

JCT-102SS-A

Twin Tank

Standard specifications



JCT-102SS-A

Model		JCT-102SS-A	
Measuring power	Shooting	Batch (kg/h)	60 ~ 120
Measurement unit			2
Hopper	Volume	Virgin Mat. (L)	55
		Crushed Mat. (L)	55
Measuring precision	Natural Mat.		± 2~3%
	Crushed Mat.		± 6~13%
Materials	Other Natural Mat.		SF-50S
	Supply Method		Screw feeder
	Crushed Mat.		SF-50S
	Supply Method		Screw feeder
Power supply		50/60Hz	AC200 220 1P
Consumption of electric power		200 VA	
Outer Dimension		W x D x H (mm)	902x524x1065
Product weight (kg)			63
Connection diameter of conveying hose (mm)		Ø38 (With easy coupler female type)	

OPTIONS

- Lower limit level switch (natural material, regrind material)
- Upper limit level switch (regrind material)
- Alarm indication (revolving light)
- Alarm Buzzer
- Receiving hopper installing board

JCT-102PP-A

Twin Tank

TWIN TANK specifications (50Hz)



JCT-102PP-A

Model		JCT-102PP-A	
Measuring power	Shooting	Batch (kg/h)	24 ~ 46
Measurement unit			2
Hopper	Volume	Virgin Mat. (L)	55
		Crushed Mat. (L)	55
Measuring precision (After measurement transportation precision)	Natural Mat.		± 2 at 340 g.
	Crushed Mat.		± 6 at 300 g.
Materials	Other Natural Mat.		MSD-45T
	Supply Method		Manual slide damper
	Crushed Mat.		MSD-45T
	Supply Method		Manual slide damper
Power supply		50/60Hz	AC200 220 1P
Consumption of electric power		30 VA	
Outer Dimension		W x D x H (mm)	902x522x1065
Product weight (kg)			65
Connection diameter of conveying hose (mm)		Ø38 (With easy coupler female type)	

OPTIONS

- Lower limit level switch (natural material, regrind material)
- Upper limit level switch (regrind material)
- Alarm indication (revolving light)
- Alarm Buzzer
- Receiving hopper installing board