

MJ5-i

Dehumidifying Dryer

The self-control " plas " function is built-in

Matsui has developed the "pas" series, equipment with "pas", forintelligence, built-in. MJ5-i autonomously determines operating conditions and constantly maintains the optimal drying conditions without any intervention by the operator.

Contributes to electricity conservation!

Since MJ5-i has a low exhaust gas temperature, air conditioning load is reduced, leading to further saving of electricity.

Concept

In consideration of energy shortages occurring in Japan and worldwide, and the fact that most electricity used in molding factories is consumed by dryers, Matsui has worked towards the development of a dryer which pursues maximum energy saving performance under our mission to "achieve factor 4 in molding factories by 2020". As a result, the MJ5-i dryer, with the self-control *plas* function built-in, has been completed. The concept behind MJ5-i is "equipment with intelligence".

Features

A maximum energy reduction of 75% has been achieved!

Conventional equipment consumes the same amount of electricity, regardless of the size of the drying load. MJ5-i has achieved energy reduction by using only the most appropriate amount of electricity according to the size of the drying load.

An industry first! Electricity is no longer worlds and

An industry first! Electricity is no longer wasted and running costs have been reduced by the self-control " plas "function!

Highest Standards in the World


A Maximum Energy Reduction of 75% has been Achieved!


¥10500

MJ5-i-150

従来機PET160℃


従来機PBT130°C







Outer Dimension



Maintenance can be carried out from the front





Standard specifications

| Model | Load capacity (Kg.) | Drying Heater output (kW) | output | Regeneration heater Capacity (kW) | blower | Required water | Breaker (Amp.) 50 Hz. | Outside dimensions W x Dx H (mm) x (mm) x (mm) | Weight (Kg) |
|--------------|------------------------|---------------------------------|--------|---|--------|----------------|--------------------------|--|-------------|
| MJ5-i-150-J | | 2.1 | 0.28 | 1.0 | 0.28 | - | 30 | 1125 x 618 x 2117 | 270 |
| MJ5-i-350-J | | 2.4 | 0.42 | 2.1 | 0.28 | - | 30 | 1191x 618 x 2203 | 290 |
| MJ5-i-650-J | | 5.4 | 1.15 | 3.1 | 0.42 | - | 50 | 1486 x 638 x 2509 | 400 |
| MJ5-i-1500-J | | 10.8 | 2.55 | 5.8 | 1.15 | - | 100 | 1910 x 914x 2689 | 690 |

- ●Weekly Timer ●Dew-point Indicator ●2 Direction Convying ●Different Supply Voltage (Excluding UL/CE) ●Custom Color (Exterior Board Only) ●Alarm Output
- Alarm Indicator Light Signal Wire Extension Power Supply Wire Extension Jet Selector JSV-38/50 (-1500) Power Meter Color Touch Screen