




JCW2-103-APH



JCW2-204-JB

Easy Maintenance



Extraction of Measuring Remaining Materials



Screw



Measuring Hopper



Vacuum Cleaner Port

Standard Specification

Model	Unit	JCW2-10		JCW2-20		
		APH	JB	APH	JB	
Power Supply	Voltage	AC200/380V, 50Hz, 3 Phase				
	Apparent Power	kVA 4.2				
	Breaker Capacity	A 20/15		30/15		
Air supply	Pressure	MPa 0.4				
	Consumption	NL/min 1				
Maximum Measuring Capacity	Number of materials mixed	2 Points	kg/h ~100	~150	~300	~400
		3 Points	kg/h ~100	~100		~350
		4 Points	kg/h ~70		~300	
Measurement Type		Batch type mass weighing by load cell				
Hopper Volume	Virgin Material	L 60				
	Regrind Material	L 60				
	MB Material	L 8.5(option)				
Measuring Hopper	Effective Volume	L 11	18			
Measuring Range		kg 0.015~3	0.015~6			
Measuring Accuracy	Virgin Materials	% ±0.5%	(F, S)			
Volume per batch		kg ~3(MAX)	~6(MAX)			
Mixing Method			Pneumatic Mixing	Mixing Drum	Pneumatic Mixing	Mixing Drum
	Effective Volume	L 8	18		14	
Outer Dimensions	W	mm 1019	1019	1155	1155	
	D	mm 618	700	618	750	
	H	mm 1714	2436	1897	2746	
Product Weight		kg 140	200	160	220	

• The above table are obtained when using pellets with a bulk density of 0.5~0.6g/cm³.
This table vary with material properties, please contact us for materials of concern.

Options


- Rotating light (without Buzzer) • Rotating light (with Buzzer) • Tower light (without Buzzer) • Tower light (with Buzzer)
- Cleaning nozzle • DIGI-PECA conveying • Leakage breaker

Alarm Indicator (Option)



Easy Maintenance


Remove remaining materials from the bottom and remove screw feeder in a single step.



Compact Volumetric type blender, synchronous measuring method.

High Performance

Rotating two screws at the same time, measure by changing the rotating speed of each screw.



Standard Specification

Model	Unit	JCT-102SS-A	
Power Supply	Voltage	AC200/220V, 50/60Hz, 1 Phase	
	Apparent Power	VA 200	
	Required breaker capacity	A 5	
Maximum Measuring Capacity	kg/h	60~120	
Measurement Type		Volumetric Type	
Hopper Volume	Virgin Material	L 55	
	Regrind Material	L 55	
Supply Method of Materials	Virgin Material	Screw Feeder SF-50S	
	Masterbatch Material		
	Regrind Material		
Volume per batch	kg	0.5~3.5	
Mixing Method		Synchronous Measuring and Feeding Method	
Outer Dimensions	W	mm 524	
	D	mm 902	
	H	mm 1,065	
Product Weight	kg	63	

Options

- Low level alarm • Material C upper level alarm • Alarm indicator • Receiving hopper installing lid